

NON-SKID COMPOUNDS

Slip resistant additive for topsides finishes



PRODUCT DESCRIPTION

Nautix NON-SKID COMPOUNDS is a special powder that can be added to 1-pack and 2-pack topside finishes (enamel and varnish) prior to application or sprinkled onto wet paint as an aid to providing a more slip-resistant finish.

The selection of different size grid improves foot adhesion on deck, and these additives do not affect finish drying times.

PRODUCT INFORMATION

| | |
|-------------|--------------|
| Flash point | Do not apply |
| Packaging | 200g - 1kg |
| Shelf life | 5 years |
| Colours | Transparent |

SAFETY INFORMATION

- Work in well-ventilated area (ensure adequate ventilation during use), wear suitable protective clothing, gloves, glasses and eye/face protection. Unprotected person must be kept away from treatment area. Dispose of protective gloves and equipment after use.
- Hazardous paint for professionals only. Read the label safety section for Health and Safety Information before application.

PAINT PREPARATION

- Estimated mixing ratio: 100 to 200 grams of non-skid compounds for 0.75 litre of paint. This ratio can be adjusted compare to the non-skid aspect targeted (the amount to mix is dependent on the non-skid texture desired).
- Shake and stir additives with the paint thoroughly before use. Leave for 10 minutes to allow bubbles to disperse.
- All substrates must be cleaned, degreased with Nautix SD, dry and free from contaminants.

HINTS & APPLICATION

- Application methods : Roller or Spray gun.
- Apply 1 regular layer with special Nautix roller (for primer and non-skid application) by crossing layers to get nice result.
- To apply to wet paint : Apply one coat of finishing paint. Apply Non-Skid Compounds with suitable dispenser or other dispersion method until desired grit onto surface has been achieved. Allow to fully cure and remove excess grit.
- Apply between 10 and 30°C (ideally inside with hygrometry rate no greater than 85%).
- Do not apply when there is a chance of condensation forming on the substrate (Dew-Point) : substrate, ambient air and product temperatures must be close.

TRANSPORT, STORAGE, AND SAFETY INFORMATION

Transport and storage

- This product should be kept in securely closed containers during transport and storage.
- Exposure to air, sun, and extreme temperatures should be avoided. For the full shelf-life of the paint, be sure that the container is firmly closed between use and the storage temperature is between 10° and 25°C. Keep out of direct sunlight.

Safety

- Before use, read the label safety section for Health and Safety Information. For further details, please contact Nautix or its distributors.
- All professional operators must wear suitable protective clothing : coveralls of a contrasting colour to the product being applied, underneath a disposable coverall with hood, suitable gloves and impervious footwear that protects the lower leg. Wear suitable respiratory equipment (such as air fed respiratory protective equipment with combined protective helmet and visor) when spraying.

Disposal

Disposal of remainders must be arranged for in consultation with the authorities. Do not discard tins or pour paint into water courses, use the facilities provided. It is best to allow paints to harden before disposal. Remainders of this product cannot be disposed of through the municipal waste route or dumped without permit.

General

The information given in this sheet is not intended to be exhaustive. Any person using the product without first making further written enquiries as to the suitability of the product for the intended purpose does so at their own risk. Nautix can accept no responsibility for the performance of the product or for any loss or damage. The information contained in this sheet is liable to modification from time to time.

Nautix – Parc d'activités Les 5 chemins – 24 rue Nicolas Appert - 56520 Guidel, France
Tel: +33.(0)2.97.65.32.69 Fax: +33.(0)2.97.65.03.54
info@nautix.com — www.nautix.com

